

Safeceiling Onecoat Ultra Matt

- Key Benefits:** Decorative fire upgrade and finish in one coat.
Protects bare and painted ceilings coated with a combination of acrylic and vinyl types of paint to achieve BS EN Class B and old Class O
These results achieved at UKAS approved Fire Test Laboratory.
- Can be used as part of a system to achieve 30 or 60 minute Fire Resistance requires specification and additional coats
Finished system provides a smooth aesthetically pleasing matt finishes for internal ceilings. (For walls see Thermoguard Safewall Systems)
- How it works:** Onecoat Ceiling Fire Paint expands in a fire to create a resilient insulating barrier.
- Fire Test:** FIRE TEST STANDARDS in UKAS and EOTA - accredited Fire Test laboratory
BS EN Class B s1 d0 (old Class O compliant) over multiple layers and combinations of waterbased painted surfaces identified as low/medium risk.
- Pack Sizes** Sold in 25 sqm, 50 sqm and 100 sqm pack sizes to aid correct application
- Coverage** Follow on can guide to coverage to enable project Certification.
- Drying Times** In normal conditions product will be touch dry in an hour and fully dry after 4 hours
- Application Conditions** Do not apply in temperatures under 8°C or above 30°C.
Maximum relative Humidity below 75%.
Surface should be at least 3°C above the dew point.
- Typical Use** This product is suitable for ceilings only
- VOC Content** Low VOC EU limit for this product (cat A/i) is 140 g/l. This product contains 16 g/lv
- Composition** Catalytic and safe vapour-emission compounds.
- Preparation** Surfaces to be clean dry and firmly adhering
Ensure good ventilation
Do not apply while condensation could occur during drying
- Application** 1 good coat applied at 10 sqm per litre over White and Off White colours
- Brush or Roller** Apply using a woven short pile roller sleeve or synthetic brush
Onecoat must be clean and fully hard dry before application of additional coats.

Safeceiling Onecoat Ultra Matt

- Spray** Pressure Pot and Gun conventional with hand-portable compressor – thin 5% water OR Airless Graco 1500, 3500 or equivalent. 3/8” line, 30 mesh filter on machine, no filter in gun. 521, 523, 621 or 623 tip
Ensure coverage is applied as per can i.e., 20 sqm can covers 20 sqm.
- Certificates** Once the works are complete, a project and area specific Certificate available after due diligence via www.thermoguard.co.uk stating any project specification number.
- Cleaning** Return as much unused material to its original container as possible. Wash brushes, rollers and guns with clean water immediately following use.
- Health and Safety** Please refer to the relevant Safety Data Sheet for full details of this product
Apply all products according to BS 6150:2019- Buildings Painting Code of Practice
Do not store this product in cold temperatures below 5°C or above 30°C.
Store in a dry secure place away from children or animals.
Dispose of in accordance with local authority waste disposal measures.
Do not pour into drains or watercourses. Reduce- Reuse- Recycle.
- Further Support** If you require any further assistance, please contact Thermoguard Technical Helpdesk on 01143 768008 option 2 or email technical@thermoguard.co.uk