



GREAT BRITISH PAINTS

TDS GBPQM

Quick Matt *by Great British Paints*

A professional quality, high opacity, quick drying, breathable flat matt emulsion for both old and new surface areas.

Performance Characteristics

White or Pastel shades from BS4800

For interior use only

Professional quality, High opacity - excellent coverage

Quick drying

Ideal for new plaster

Water-based

Economical

Not suitable for areas subjected to heavy condensation.

Preparation

All surfaces must be painted should be clean, dry and free from loose and flaking material.

Prime bare surfaces with 10% thinned with water 1st.

Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. Do not apply when the air or substrate temperatures are likely to fall below 8°C or when the relative humidity is above 80% during application or the drying period.

Application

Easy to apply by brush or roller. Also suitable for application by spray (see below). If more than one can of colour is to be used in the same area, intermix before use. Ensure good ventilation during application and drying. Spreading Rate up to 14 square meters/litre per coat depending on the nature and porosity of the surface being painted.

Spray & Thinning Application

Thinning: sealing new or bare surfaces: up to 1.5 part clean water to 10 parts paint @ 2500 PSI / 172 bar with a 527 tip.

 01524 944701

 PROTECTIONPAINTS.COM

 SALES@PROTECTIONPAINTS.COM



GREAT BRITISH PAINTS

Airless Spray:

Un-thinned: Spray @ 3000 PSI / 207 bar with 527 tip.

Thinned: 1 part clean water to 10 parts paint spray @ 2500 PSI /172 bar with 527 tip.

Drying Time

Under normal drying, touch dry in 2 hours, Recoat-able after 4 hours.

Allow for adequate ventilation during the drying period.

Shelf Life

Up to 18 months if stored correctly in an unopened container.

Cleaning

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

Precautions

Keep out of reach of children.

In case of contact with eyes wash immediately with plenty of water.

Remove splashes from skin with soap and water or a recognised hand cleaner.

Protect from freezing.

Do not apply paint if there is a risk of heavy rain or frost.

Do not use near fishponds.

 01524 944701

 PROTECTIONPAINTS.COM

 SALES@PROTECTIONPAINTS.COM