

Enterprise Park Wigwam Lane Hucknall NG15 7SZ 01524 944713 Emergency nobusiness hours. 01524 944713

## SAFETY DATA SHEET

Protection paints Asbestos Encapsulating Coat - GENERAL

**Compilation date:** 7/01/2024 Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PROTECTION PAINTS Asbestos Encapsulating Coat - GENERAL

**1.2.** Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: An air drying water borne flame retardant coating for rigid boards containing asbestos and

other surfaces within buildings. apply by brush, roller or spray

#### 1.3. Details of the supplier of the safety data sheet

Company name: Protection Paints Ltd

Wigwam lane

Hucknall

NG15 7SZ

United Kingdom

Tel: 01524 944713

Email: sales@protectionpaints.com

1.4. Emergency telephone number

Emergency tel: 01524 944713

(office hours only)



## Section 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification under CHIP: This product has no classification under CHIP.

#### 2.2. Label elements

Label elements under CHIP:	
Hazard symbols:	Symbol not required.
Safety phrases:	S2: Keep out of the reach of children.
	S7: Keep container tightly closed.
	S20/21: When using do not eat, drink or smoke.
	S24/25: Avoid contact with skin and eyes.
	S27/28: After contact with skin, take off immediately all contaminated clothing, and wash
	immediately with plenty of soap and water or proprietary skin cleaner.
	S29/35: Do not empty into drains; dispose of this material and its container in a safe way.
	S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
	S38: In case of insufficient ventilation, wear suitable respiratory equipment.
Precautionary phrases:	Safety data sheet available for professional user on request.

#### 2.3. Other hazards

Other hazards: Not applicable.

**PBT:** This product is not identified as a PBT substance.

## Section 3: Composition/information on ingredients

## 3.2. Mixtures

#### Hazardous ingredients:

## ZINC BORATE - REACH registered number(s): 01-2119691658-19-0001

EINECS	CAS	CHIP Classification	CLP Classification	Percent
235-804-2	138265-88-0	N: R50	Aquatic Acute 1: H400	1-10%

## PROPANE DIOL - REACH registered number(s): 01-2119456809-23-0003

200-338-0	57-55-6	Substance with a Community	-	1-10%
		workplace exposure limit.		



## Section 4: First aid measures

## 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Do NOT use solvent or thinners

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

- **Ingestion:** Do not induce vomiting. Wash out mouth with water. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.
- Inhalation: Remove to fresh air Keep the patient warm and at rest If unconscious and breathing is OK, place in the recovery position. If unconscious, check for breathing and apply artificial respiration if necessary. Consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

 Skin contact: There may be mild irritation at the site of contact. repeated exposure may cause skin dryness and/or cracking

 Eye contact: There may be irritation and redness.

 Ingestion: No data available.

 Inhalation: No data available.

 Delayed / immediate effects: No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: In all cases of doubt,or when symptoms persist seek medical attention. Show this safety data sheet to the doctor in attendance.

#### Protection Paints ASBESTOS ENCAPSULATING COAT - GENERAL

#### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: extinguish with foam, dry powder, carbon dioxide or water fog Suitable extinguishing

media for the surrounding fire should be used. Use water spray to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes. Do not allow run off to enter watercourses or drains

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid. Avoid breathing any vapours

## 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

## 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

#### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in

the air. Avoid skin and eye contact Smoking, eating and drinking should be prohibited in

mixing and application area Do not allow to enter drains or watercourses

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep container tightly closed. store between 5 and 30oC in a dry well ventilated area

Suitable packaging: Must only be kept in original packaging.

## 7.3. Specific end use(s)

Specific end use(s): the identified uses of this product are detailed in section 1

Protection Paints ASBESTOS ENCAPSULATING COAT - GENERAL

Page: 3

-

## Section 8: Exposure controls/personal protection

## 8.1. Control parameters

## Hazardous ingredients:

## ZINC BORATE

## Workplace exposure limits:

 State
 8 hour TWA
 15 min. STEL
 8 hour TWA
 15 min. STEL

 UK
 10 mg/m3

\_

**Respirable dust** 

-

#### PROPANE DIOL

UK

### 8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

150 ppm

## 8.2. Exposure controls

Engineering measures: Ensure all engineering measures mentioned in section 7 of SDS are in place. Ensure

there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection must be used if the general level exceeds the recommended

occupational exposure limit

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place. Prevent

from entering in public sewers or the immediate environment.

#### Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	Various		
Odour:	Characteristic odour		
Solubility in water:	Miscible		
Viscosity:	Viscous		
Kinematic viscosity:	1-2 poise		
Viscosity test method:	Cone & plate @ 20 oC		
Boiling point/range°C:	100	Flammability limits %: lower:	not flammable
Flash point°C:	not relevant	Relative density:	1.3 - 1.4
pH:	8.5 - 9.0	VOC g/l:	30 grammes/litre maximum

## Protection Paints ASBESTOS ENCAPSULATING COAT - GENERAL

## 9.2. Other information

## Other information: VOC Content: EU limit for this product is(CatA/i) is 500 g/litre

## Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions. In a Fire, hazardous

composition products may be produced

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### **ZINC BORATE**

DERMAL	RAT	LD50	>2000	mg/kg
DUST/MIST	RAT	4H LC50	0.002	g/l
ORAL	RAT	LD50	3500	mg/kg

#### **PROPANE DIOL**

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>20,000	mg/kg
VAPOURS	RBT	1H LC50	317.4	mg/l

Toxicity values: No data available.

#### Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact. repeated exposure may cause skin

dryness and/or cracking

Eye contact: There may be irritation and redness.

Protection Paints ASBESTOS ENCAPSULATING COAT - GENERAL

**Page:** 5

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: No data available.

## Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

## 12.2. Persistence and degradability

Persistence and degradability: No data available.

#### 12.3. Bio accumulative potential

Bio accumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

#### 12.6. Other adverse effects

Other adverse effects: No data available.

#### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Dispose of waste and residues according to local authority requirements

Waste code number: 08 01 12

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

#### 14.1. UN number

UN number: not classified

#### 14.2. UN proper shipping name

Shipping name: not classified

#### 14.3. Transport hazard class(es)

Transport class: not classified (not+classified)

#### 14.4. Packing group

Packing group: not classified

## Protection Paints ASBESTOS ENCAPSULATING COAT - GENERAL

**Page:** 6

#### 14.5. Environmental hazards

#### Environmentally hazardous: No

Marine pollutant: No

#### 14.6. Special precautions for user

Special precautions: Always transport in upright sealed containers Ensure that persons transporting the

product what to do in the event of an accident or spillage

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk: not Relevant

## Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

## Section 16: Other information

Other information			
Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No			
	453/2010.		
	* indicates text in the SDS which has changed since the last revision.		
Phrases used in s.2 and 3:	H400: Very toxic to aquatic life.		
	R50: Very toxic to aquatic organisms.		
Legal disclaimer:	Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive		
	and shall be used only as a guide. This company shall not be held liable for any		
	damage resulting from handling or from contact with the above product.		

Protection Paints ASBESTOS ENCAPSULATING COAT - GENERAL

Page: 7